

ADDCON OFFERS SCIENCE

Top layer or lower layers in the bunker – a huge difference



During feed-out the whole silage surface seems to be uniform quite often. Reheating and spoiling of the silage are often unseen in the top layer or at the edges of the bunker. The compaction at the top layer is always lower than in middle and lower areas of the bunker respectively, because the material at the surface rebounds. Especially in silage pills but in bunkers also, the edge or flanks are mostly not well compacted.

However, an airtight sealing is necessary for the ensiling process. Carbohydrates will be metabolized to fermentation acids and CO_2 under anaerobic conditions. During the feed-out period the CO_2 can easily flow out of the areas of lower compaction and fresh air, O_2 is sucked in. The O_2 activates yeasts and moulds and they start their aerobic metabolism, which causes spoiling and reheating of the silage.





On-top and center location in a bunker are often characterized by differences in the feed material. Analytical results of farm bunkers show that corn silage has often a higher dry matter (DM) at the top layer which results in a lower intensity of fermentation accompanied by a lower concentration of fermentation acids. *Lactobacillus buchneri* metabolizes less acetic acid under these conditions! However, acetic acid is needed to inhibit the growth of yeasts. Lower amounts of acetic acid can become critical when older and riper material high in starch and digestibility will be put on top of the bunker.

Lactic acid will be metabolized by yeasts during the reheating process. Here, the content of lactic acid is identically in both layers (tab.1). There has been no reheating in that silage.

At the first glance there is no need to worry. But the lower content of acetic acid in the top layer in combination with a higher DM, lower compaction and higher starch concentration poses a risk of reheating. Because of a lower fermentation activity at top-layer, inoculants cannot guarantee a protection from reheating.

If a higher DM and lower compaction can be expected in the top layer the use of **salts** like KOFASIL STABIL, MAIS KOFASIL liquid or KOFASIL SALT is recommended. Chemical additives have a higher protection against reheating compared to inoculants.

Table 1: Differences of feed and fermentation parameters between on-top and lower layers in a maize bunker caused by different plant ripeness.

	DM (g/kg)	starch (g/kg DM)	ELOS (%)	pH	lactic acid (% DM)	acetic acid (% DM)
top layer	335	320	66	4,0	5,0	1,8
center layer	310	290	63	3,9	5,0	2,9

ELOS = enzyme soluble organic matter



For further product information or pricing, contact the Australian Distributor
Prime Animal Health
 Tel: 0455 505 520 Email: Shaun@primeanimalhealth.com.au



Ober_oder_unten_in_Silo_TRIAL_GB_0522_frho



ADDCON GmbH
 Parsevalstraße 6,
 06749 Bitterfeld-Wolfen,
 Germany
 Phone: +49 3493 96787 00
 Fax: +49 3493 96787 70
 www.addcon.com

ADDCON EUROPE GmbH
 Areal E / Säurestraße 1,
 06749 Bitterfeld-Wolfen,
 Germany
 Phone: +49 3493 96787 00
 Fax: +49 3493 96787 70
 www.addcon.com

ADDCON NORDIC A/S
 Postboks 1138 Herøya
 3905 Porsgrunn
 Norway
 Phone: +47 35 56 41 00
 Fax: +47 35 56 41 01
 www.addcon.com

ADDCON Asia Ltd.
 Workshop 2, 12/F,
 Winning Centre
 29 Tai Yau Street, San Po Kong
 Kowloon, Hong Kong
 Phone: +852 2368 0091
 Fax: +852 2368 0127
 www.addcon.com

ADDCON (Dalian)
Environmental Products Ltd.
 Room 4403, Tower A, Times Square,
 No. 50 Renmin Road,
 Zhongshan District,
 Dalian 116001, China
 Phone: +86 411 82538001
 Fax: +86 411 82538010
 www.addcon.com